
OpenOcean water.

Open Ocean Modular Water • Quencher Series

QUENCHER
12 Volt DC

Data Sheet




September 2026

Phone +64 21 167 6269
Email info@openoceanwater.com
Website openoceanwater.com

OpenOcean water.





1. Data Sheet

The major components are assembled in modular form to best utilise your available space. These components are universal in nature and many of them are available worldwide, an important feature for a vessel operating internationally. Open Ocean keeps circuit boards, fancy controls and flashing lights off their products to provide the most reliable watermaker possible.

This reverse osmosis desalination plant utilises a commercial-grade high pressure pump, coupled to a 1 hp, 12 Volt DC electric motor. This supplies high pressure, pre-filtered sea water to a reverse osmosis membrane that produces approx. 70 litres of potable water per hour, using approx. 56 amps at 12.5 Volts, from sea water at 25 degrees C and a salinity of 35,000 ppm, at an operating pressure of 800–850 psi.

2. Dimensions

- High pressure pump with electric motor 340mm wide x 540mm long x 220mm high
- Membrane vessel 90mm wide x 1190mm long
- Control panel 275mm high x 185mm wide
- Sample/tank valve panel 130mm wide x 75mm high
- Boost pump, 12V 100mm high x 100mm wide x 70mm deep
- Sea water filters 400mm high x 320mm wide x 130mm deep
- Flush filter 400mm high x 370mm wide x 130mm deep

3. Options

Autoflush

Automatically flushes fresh water through the system every 7 days, preserving the membranes — especially good for boaters who don't get back to their boats as often as they mean to.



20 Micron Pre-filter


For systems that will operate in water with high levels of organics. Filters out plankton and silt before it reaches the 5 micron pre-filter, extending its service life.



Specifications

- 12 Volt DC electric motor
- 70 litres per hour @ approx. 56 amps @ 12.5 constant volts
- Commercial quality reverse osmosis stainless steel high pressure pump
- Reverse osmosis membranes and 2000 psi carbon fibre pressure vessel(s)
- 5 micron polyester pleated washable pre-filter for cost-effective, long-life filtration
- Fresh water flush facility: charcoal filter connects to your onboard pressure water system to flush the watermaker with fresh water
- Pressure relief valve — protects components from accidental over-pressure situations
- Test, rejection and regulation valves
- High pressure hose / nylon non-corrosive tubing — can be cut and fitted aboard
- 12 Volt centrifugal sea water rated low pressure boost pump
- All you need to provide is a sea strainer, access to the ship's water tanks, low pressure hoses, and any mounting surfaces required to position the Open Ocean components

4. Component Schematic



Open Ocean Group Ltd
8 Haszard Street, Waihi, New Zealand
Phone +64 21 167 6269
info@openoceanwater.com
openoceanwater.com